

# Bobema Polymers

## BBM-EVA-601



High ambient temperatures and high traffic loads will lead to rutting and bleeding of asphalt pavements. This effect can be minimized by adding BBM-EVA-601 polymer to the asphalt binder.

BBM-EVA-601 is a pure EVA modification, compatible with most types of bitumen used in the road construction industry.

Adding BBM-EVA-601 will improve the mechanical properties of the asphalt pavement, such as increasing the resistance to rutting and increasing the durability of the pavement, and may lead to reduced pavement thickness.



Further BBM-EVA-601 will improve the resistance to jet fuels and improve the binder low temperature flexibility and cohesion.

BBM-EVA-601 can be pre-blended with bitumen or poured directly into the asphalt mixer.

Standard mix design is needed to determine the optimum BBM-EVA-601 content for different end-use properties.



**Bobema Nederland B.V.**  
special products for civil engineering  
and construction industry

P.O. Box 552  
1620 AN Hoorn  
The Netherlands  
Tel.: +31 229 211011  
Fax: +31 229 212614  
Email: [info@bobema.com](mailto:info@bobema.com)  
Internet: [www.bobema.com](http://www.bobema.com)

Bobema Nederland B.V. is a Dutch company. All information is given in good faith and is correct to the best of our knowledge. Information given must be verified independently by the user and does not form part of any contract with Bobema Nederland B.V.